



Rockingham Raceway

1/24th Scale RETRO CAN-AM CHAMPIONSHIP

The following cars will be eligible for the Championship

Any Car built to current UKRRA Can-Am rules

For full details see the CSCRA website - www.cscra.co.uk

Or the ABSlotsport website - www.abslotsport.biz

Race control may also permit cars built to the following rules to race but they will not be eligible for the Club Championship

Rockingham 1/24th Production Cars fitted with a Can-Am style body.

Summary of the basic UKRRA Can-Am rules

1. Chassis

- a. Any scratch built or kit built, inline, 'Brass and Wire' chassis that complies with the UKRRA Can-Am Rules.

2. Motor

- a. Only the following motors are permitted:
JK Falcon 7, TSR (D3) Falcon, JK Hawk 7, Trinity Evil 9, Fast Ones Demon and Slick 7 S7-588 Mini Motor.

3. Body

- a. Any vac' formed (Lexan, PETG etc) 1/24th scale replica of a real two seat, open cockpit, Sports Car built and raced before the end of 1969 can be used.
- b. Bodies must be fully painted, detailed and numbered in accordance with UKRRA guidelines.
- c. Bodies must cover the entire chassis, including the guide, the motor and the wheels, tyres and gears when viewed from directly above.
- d. Cockpit and wheel arch openings must be cut out as on the real car.
- e. An interior, including a driver, must be fitted and no part of the chassis or running gear may be visible through the windscreen or windows.

4. Dimensions

- a. Maximum Height of the rear body must not exceed 34.93mm.
- b. Any add on rear spoiler must not exceed 12.7mm in height.
- c. Overall Width of the entire car must not exceed 82.55mm.
- d. Overall chassis width, including wheels and tyres must not exceed 79.38mm.
- e. Minimum Ground Clearance: Front – 0.38mm. Rear – 1.27mm.
- f. Wheels and Tyres.
Rear: Maximum width – 20.57mm. Minimum diameter – 20.64mm.
Front: Minimum Width – 5.72mm. Minimum diameter – 19.05mm.